



Sales Specification

Perchloroethylene (C₂Cl₄)

Fluorocarbon (PTAP) Grade

| <u>COMPONENT</u> | <u>SPECIFICATIONS</u> |
|-----------------------------|-----------------------|
| Perchloroethylene, wt% | 99.99 min. |
| Color, APHA | 10 max. |
| Appearance (ASTM D 3741-B) | Passes Test |
| Specific Gravity @ 25/25°C | 1.617 - 1.621 |
| Nonvolatile Residue, ppm | 10 max. |
| Water, ppm | 25 max. |
| Chlorides, ppm | 1 max. |
| Free Halogens (ASTM D 4755) | Passes Test |

TYPICAL PROPERTIES

Distillation Range, 760 mm, °C 120.6 - 121.6

Typical properties are listed for information only and are not to be considered as specification requirements. These items are not analyzed on a routine basis. Product meeting the specification test items will exhibit the listed typical properties.

CONTAINERS:

Tank Cars - Lined 20,000-gallon cars and maximum weight load of 197,000 lbs.

Tank Trucks (stainless) - Shell capacity or maximum weight load of 3,600 gallons

Drums - 700-pound net, 747-pound gross weight drums, UN 1A1/Y1.8/300

Form#: 587 01/2026